

Claims

1. Steam generator (1) in which an evaporator/once-through heating area (8) is disposed within a heating-gas duct (6) through which a heating gas can flow in an approximately horizontal direction (x), said evaporator/once-through heating area (8) comprising a number of steam-generator tubes (12) which are connected in parallel and through which a flow medium (D,W) can flow and being configured such that a steam-generator tube (12) which is heated to a greater extent compared with a further steam-generator tube (12) of the same evaporator/once-through heating area (8) has a higher throughput of the flow medium (W) than said further steam-generator tube (12),
- characterized in that a discharge collector (20) which is connected downstream of the steam-generator tubes (12) of the evaporator/once-through heating area (8) on the flow-medium side, is oriented with its longitudinal axis essentially parallel to the heating-gas direction (x).
2. Steam generator (1) according to Claim 1, wherein the respective discharge collector (20) is fashioned essentially as a cylindrical body.
3. Steam generator (1) according to Claim 1 or 2, the evaporator/once-through heating area (8) of which comprises a number of tube layers (14) arranged one behind one another, viewed in the heating-gas direction (x), each of which tube layers is formed from a number of steam-generator tubes (12) arranged side-by-side, viewed in the heating-gas direction (x).
4. Steam generator (1) according to Claim 3, to the evaporator/once-through heating area (8) of which is assigned a number, corresponding to the number of steam-generator tubes (12) in each tube layer (14), of discharge collectors (20),

oriented with their longitudinal axis essentially parallel to the heating-gas direction (x), whereby one steam-generator tube (12) of each tube layer (14) discharges into each discharge collector (20).

5

5. Steam generator (1) according to any one of Claims 1 to 4, downstream of the evaporator/once-through heating area (8) of which a further evaporator/once-through heating area (10) is disposed on the flow-medium side.

10

6. Steam generator (1) according to Claim 5, the further evaporator/once-through heating area (10) of which comprises a number of steam-generator tubes (22) which are connected in parallel and through which a flow medium (D, W) flows and is configured such that a steam-generator tube (22) which is heated to a greater extent compared with a further steam-generator tube (22) of said further evaporator/once-through heating area (10) has a higher throughput of the flow medium (D, W) compared with said further steam-generator tube (22).

20

7. Steam generator (1) according to Claims 5 or Claim 6, wherein the steam-generator tubes (22) forming the further evaporator/once-through heating area (10) each have a downtake section (32) which is disposed approximately vertically and through which the flow medium (W) can flow in a downward direction, and an uptake section (34) which is connected downstream of said downtake section on the flow-medium side, which is disposed approximately vertically and through which the flow medium (W) can flow in an upward direction.

30

8. Steam generator (1) according to any one of Claims 5 to 7, the evaporator/once-through heating area (8) of which is dimensioned such that, during operation, the flow medium (D, W) flowing into the further once-through heating area (10) connected downstream thereof has a flow velocity greater than the minimum velocity required in order to carry along any steam bubbles present there.

35

9. Steam generator (1) according to any one of Claims 5 to 8,
wherein the discharge collector (20) or each discharge
collector (20) of the evaporator/once-through heating area (8)
5 is integrated in a structural unit (40) with a respectively
assigned entry collector (24) of the further once-through
evaporating heating unit (10) connected downstream on the
flow-medium side.
- 10 10. Steam generator (1) according to any one of Claims 5 to 9,
the discharge collector(s) (20) of which is/are disposed above
the heating-gas duct (6).
- 15 11. Steam generator (1) according to any one of Claims 1 to
10, upstream of which a gas turbine is connected on the
heating-gas side.